


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 72.87 lm/W			
MODEL	CLU701 1002	I _{max} (cd)	4903	S/MH (C0/180)	0.27
NOMINAL POWER (W)	8W	LOR (%)	100.0	S/MH (C90/270)	0.28
RATED VOLTAGE (V)		TOTAL FLUX (lm)	674.17	η UP, DN (C0-180)	0.2, 56.2
NOMINAL FLUX (lm)	674.175	CIE CLASS	DIRECT	η UP, DN (C180-360)	0.1, 43.5
LAMPS INSIDE	1	η up (%)	0.3	CIBSE SHR NOM	0.00
TEST VOLTAGE (V)	220.2	η down (%)	99.7	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C90	C180	C270					γ	Φ zone	Φ total	%lum,lamp
10	2424	2265	1609	1642					0- 10	320.1	320.1	47.5,47.5
20	389.9	341.4	265.6	275.6					10- 20	224.1	544.2	80.7,80.7
30	93.57	89.14	70.60	74.82					20- 30	75.64	619.9	91.9,91.9
40	31.93	29.46	26.27	27.30					30- 40	30.36	650.2	96.4,96.4
50	15.97	9.462	13.79	10.98					40- 50	15.47	665.7	98.7,98.7
60	3.978	0.3626	3.005	0.4105					50- 60	5.775	671.5	99.6,99.6
70	0.0960	0.0139	0.0484	0.0227					60- 70	0.5257	672.0	99.7,99.7
80	0	0	0	0.0000					70- 80	0.0078	672.0	99.7,99.7
90	0	0	0	0					80- 90	0.0000	672.0	99.7,99.7
100	0.0087	0	0.0035	0					90-100	0.0032	672.0	99.7,99.7
110	0	0.0017	0	0					100-110	0.0008	672.0	99.7,99.7
120	0.0122	0.0192	0.0314	0.0070					110-120	0.0083	672.0	99.7,99.7
130	0.0592	0.0610	0.0768	0.0505					120-130	0.0316	672.0	99.7,99.7
140	0.2091	0.2182	0.1867	0.1465					130-140	0.0878	672.1	99.7,99.7
150	0.7960	0.8197	0.5217	0.4775					140-150	0.2169	672.4	99.7,99.7
160	2.847	2.973	2.044	2.056					150-160	0.6557	673.0	99.8,99.8
170	3.563	3.634	3.050	3.067					160-170	0.8789	673.9	100,100
180	2.649	2.616	2.647	2.617					170-180	0.2901	674.2	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 659.12 lm

%lum = 97.8%

%lamp = 97.8%

Conical surface Flux(120deg): 671.47 lm

%lum = 99.6%


%lamp = 99.6%

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Xie Bi
 Test Date:2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
 Humidity:65.0%
 Test Distance:6.810m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	0	0
80	0	0
75	0	1
70	56	8
65	256	25
60	1591	145
55	3759	877
50	4970	2944
45	6244	5572


C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.13	1.11	1.10	1.11	1.09	1.08	1.07	1.06	1.04	1.03	1.02	1.01	.00	.99	.98	.97
2.0	1.08	1.05	1.03	1.06	1.04	1.02	1.03	1.01	.99	1.00	.99	.97	.98	.96	.95	.94
3.0	1.04	1.00	.97	1.02	.99	.97	.00	.97	.95	.98	.95	.94	.95	.94	.92	.91
4.0	.00	.96	.93	.99	.95	.93	.97	.94	.92	.95	.93	.91	.93	.91	.90	.88
5.0	.97	.93	.90	.96	.92	.89	.94	.91	.89	.93	.90	.88	.91	.89	.87	.86
6.0	.94	.90	.87	.93	.89	.87	.92	.88	.86	.90	.88	.85	.89	.87	.85	.84
7.0	.91	.87	.84	.90	.87	.84	.89	.86	.84	.88	.85	.83	.87	.85	.83	.82
8.0	.89	.85	.82	.88	.84	.82	.87	.84	.82	.86	.83	.81	.85	.83	.81	.80
9.0	.86	.83	.80	.86	.82	.80	.85	.82	.80	.84	.81	.79	.84	.81	.79	.78
10.0	.84	.81	.78	.84	.80	.78	.83	.80	.78	.83	.80	.78	.82	.79	.77	.77



C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Xie Bi
 Test Date:2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
 Humidity:65.0%
 Test Distance:6.810m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coeffcients(WEC)										
0.0																	
1.0	.132	.075	.024	.125	.071	.023	.113	.065	.021	.101	.058	.019	.091	.052	.017		
2.0	.122	.067	.021	.117	.064	.020	.106	.059	.018	.097	.054	.017	.088	.050	.016		
3.0	.114	.060	.018	.109	.058	.018	.100	.054	.017	.092	.051	.016	.085	.047	.015		
4.0	.106	.055	.016	.102	.054	.016	.095	.050	.015	.088	.047	.014	.082	.045	.014		
5.0	.100	.051	.015	.096	.049	.014	.090	.047	.014	.084	.045	.013	.079	.042	.013		
6.0	.094	.047	.013	.091	.046	.013	.086	.044	.013	.081	.042	.012	.076	.040	.012		
7.0	.089	.044	.012	.086	.043	.012	.082	.041	.012	.077	.040	.012	.073	.038	.011		
8.0	.084	.041	.012	.082	.040	.011	.078	.039	.011	.074	.038	.011	.071	.036	.011		
9.0	.080	.039	.011	.078	.038	.011	.075	.037	.010	.071	.036	.010	.068	.035	.010		
10.0	.076	.037	.010	.075	.036	.010	.072	.035	.010	.069	.034	.010	.066	.033	.010		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.193	.193	.193	.165	.165	.165	.113	.113	.113	.065	.065	.065	.021	.021	.021	
1.0	.170	.160	.151	.146	.137	.130	.100	.095	.090	.057	.055	.052	.018	.018	.017	
2.0	.152	.135	.121	.130	.116	.105	.089	.081	.073	.051	.047	.043	.017	.015	.014	
3.0	.137	.116	.099	.117	.100	.086	.081	.069	.060	.047	.041	.035	.015	.013	.012	
4.0	.124	.100	.082	.106	.087	.071	.073	.060	.050	.042	.035	.030	.014	.012	.010	
5.0	.113	.088	.069	.097	.076	.060	.067	.053	.042	.039	.031	.025	.013	.010	.008	
6.0	.104	.078	.059	.090	.067	.051	.062	.047	.036	.036	.028	.022	.012	.009	.007	
7.0	.096	.070	.051	.083	.060	.044	.057	.042	.031	.033	.025	.019	.011	.008	.006	
8.0	.090	.063	.044	.077	.054	.039	.053	.038	.027	.031	.023	.016	.010	.007	.005	
9.0	.084	.057	.039	.072	.049	.034	.050	.035	.024	.029	.021	.014	.009	.007	.005	
10.0	.079	.052	.034	.068	.045	.030	.047	.032	.021	.027	.019	.013	.009	.006	.004	

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm												
NAME: 89014LED					TYPE:			WEIGHT:				
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700					DIM.:			SERIAL No.:				
MFR.: CETTIGA					SUR.:			Shielding Angle:				
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3		
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3		
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2		
Room dimensions		Viewed crosswise					Viewed endwise					
x = 2H y = 2H		11.3	11.9	11.5	12.0	12.2	10.3	10.9	10.5	11.0	11.2	
		3H	11.1	11.7	11.4	11.9	12.1	10.1	10.7	10.3	10.9	11.1
		4H	11.0	11.6	11.3	11.8	12.0	10.0	10.6	10.3	10.8	11.0
		6H	11.0	11.5	11.2	11.7	12.0	9.9	10.5	10.2	10.7	10.9
		8H	10.9	11.4	11.2	11.7	11.9	9.9	10.4	10.2	10.7	10.9
		12H	10.9	11.4	11.2	11.6	11.9	9.9	10.3	10.2	10.6	10.9
4H	2H	11.1	11.6	11.3	11.8	12.1	10.1	10.7	10.4	10.9	11.1	
	3H	10.9	11.4	11.2	11.7	11.9	9.9	10.4	10.2	10.7	11.0	
	4H	10.8	11.3	11.2	11.6	11.9	9.8	10.3	10.2	10.6	10.9	
	6H	10.7	11.1	11.1	11.4	11.8	9.7	10.1	10.1	10.5	10.8	
	8H	10.7	11.0	11.0	11.4	11.7	9.7	10.0	10.1	10.4	10.8	
	12H	10.6	10.9	11.0	11.3	11.7	9.6	10.0	10.0	10.3	10.7	
8H	4H	10.7	11.0	11.0	11.4	11.7	9.7	10.0	10.1	10.4	10.8	
	6H	10.5	10.8	11.0	11.2	11.7	9.6	9.9	10.0	10.3	10.7	
	8H	10.5	10.8	10.9	11.2	11.6	9.5	9.8	9.9	10.2	10.6	
	12H	10.4	10.6	10.9	11.1	11.6	9.4	9.7	9.9	10.1	10.6	
12H	4H	10.6	10.9	11.0	11.3	11.7	9.6	10.0	10.0	10.3	10.7	
	6H	10.5	10.8	10.9	11.2	11.6	9.5	9.8	9.9	10.2	10.6	
	8H	10.4	10.6	10.9	11.1	11.6	9.4	9.7	9.9	10.1	10.6	
Variations with the observer position at spacings:												
S = 1.0H		+ 2.1 / - 4.3					+ 2.5 / -11.8					
1.5H		+ 2.5 / - 3.0					+ 3.0 / - 4.9					
2.0H		+ 3.9 / -12.5					+ 5.5 / -18.6					

CIE Pub.117, 674.2 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -1.4)
Area: 0.005 m2

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	89	83	80	89	83	80	88	83	79	76
0.80	96	91	88	96	91	87	95	90	87	84
1.00	101	95	92	100	95	92	98	95	91	87
1.25	104	99	96	103	99	96	101	98	95	91
1.50	107	102	99	106	102	99	103	100	98	93
2.00	109	105	102	108	104	102	105	102	100	95
2.50	111	107	104	109	106	104	106	104	102	96
3.00	112	109	106	110	108	105	107	105	103	97
4.00	114	112	110	112	110	108	108	107	105	98
5.00	115	113	112	113	111	110	109	108	107	99
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: Xie Bi
 Test Date: 2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.286
 Humidity: 65.0%
 Test Distance: 6.810m [K=1.0000]
 Remarks:

AAI Figure

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Xie Bi
Test Date: 2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity: 65.0%
Test Distance: 6.810m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	206
L_0~180 (75) av	0
L_0~180 (85) av	0
L_90~270 (65) av	32
L_90~270 (75) av	5
L_90~270 (85) av	0
L_45 (65) av	94
L_45 (75) av	3
L_45 (85) av	0

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
 C Interval: 90.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:Xie Bi
 Test Date:2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
 Humidity:65.0%
 Test Distance:6.810m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: Xie Bi
Test Date: 2023-11-15

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity: 65.0%
Test Distance: 6.810m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:232.49V I:0.0440A P:9.2520W PF:0.9052 Freq:50.00Hz Lamp Flux:674.175x1 lm		
NAME: 89014LED	TYPE:	WEIGHT:
SPEC.:P-89014LED-8W3015-CI25031R90-HEK700	DIM.:	SERIAL No.:
MFR.: CETTIGA	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	90	180	270															
0	4894	4882	4894	4882															
5	4469	4392	3828	3837															
10	2424	2265	1609	1642															
15	915	809	602	612															
20	390	341	266	276															
25	184	169	131	139															
30	93.6	89.1	70.6	74.8															
35	52.8	49.3	40.6	42.5															
40	31.9	29.5	26.3	27.3															
45	22.1	19.7	18.9	19.6															
50	16.0	9.46	13.8	11.0															
55	10.8	2.51	8.78	3.38															
60	3.98	0.36	3.01	0.41															
65	0.54	0.05	0.33	0.08															
70	0.10	0.01	0.05	0.02															
75	0.00	0.00	0.00	0.01															
80	0.00	0.00	0.00	0.00															
85	0.00	0.00	0.00	0.00															
90	0.00	0.00	0.00	0.00															
95	0.00	0.00	0.00	0.00															
100	0.01	0.00	0.00	0.00															
105	0.00	0.00	0.00	0.00															
110	0.00	0.00	0.00	0.00															
115	0.00	0.03	0.02	0.00															
120	0.01	0.02	0.03	0.01															
125	0.03	0.03	0.05	0.02															
130	0.06	0.06	0.08	0.05															
135	0.11	0.12	0.12	0.09															
140	0.21	0.22	0.19	0.15															
145	0.36	0.41	0.25	0.23															
150	0.80	0.82	0.52	0.48															
155	1.70	1.80	1.11	1.11															
160	2.85	2.97	2.04	2.06															
165	3.64	3.73	2.87	2.86															
170	3.56	3.63	3.05	3.07															
175	3.02	2.98	2.77	2.70															
180	2.65	2.62	2.65	2.62															

C Range: 0 - 360DEG
C Interval: 90.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:Xie Bi
Test Date:2023-11-15

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.286
Humidity:65.0%
Test Distance:6.810m [K=1.0000]
Remarks: